





Downlight for enhanced lighting requirements. For illuminating large areas with high mounting heights. Robust, chlorine-resistant housing made of die-cast aluminium with optional lateral cable gland.



Technical data

Material:	die-cast aluminum
Illuminant:	1 x 8W LED-module
Luminous flux:	801 lm
Nominal voltage DC:	24 V $\pm$ 25 %
Nominal current DC:	430 mA

Effective power:	10,4 W
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

3.0	5.5	12.2
4.0	6.5	15.1
5.0	7.2	17.4
6.0	7.8	19.0
7.0	8.2	20.4
8.0	8.4	21.5
9.0	8.4	22.5
10.0	8.1	23.5
11.0	7.4	23.8
12.0	6.5	23.9
13.0	5.2	23.7

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

4.0	4.8	11.5
6.0	5.5	15.4
8.0	5.8	18.2
10.0	5.8	20.1
12.0	5.5	21.5
14.0	5.4	21.7
16.0	4.0	19.5
18.0	3.5	15.9
20.0	3.0	14.7
22.0	3.0	12.7
24.0	2.5	10.8

Articles


SN 8500 -08 SHB LED 24V/S

Colors	HWF 9006	HWF (special)
Art. no.	101358936	101359037

ceiling mounting


Light colour: 4000 K

Protection category:
IP65




Ringbolts for SN 8500/24xx

Art. no. 100912635




Recessed ceiling frame SN 8500, HWF 9006

Art. no. 101432593



Wall bracket SN 8500, RAL 9006

Art. no. 101432795



Name	Accessories	Art. no.
Haube SN 8500	spare part	50207
L-JET 7/S-max. 24V DC650mA const	spare part	101422691
LM 8500-08 1/4K KB150 LED Modul	spare part	104429590
M20 cable glands (PU 2 pcs.)	optional	104661784
Recessed ceiling frame SN 8500, HWF 9006	optional	101432593
Ringbolts for SN 8500/24xx	optional	100912635
Wall bracket SN 8500, RAL 9006	optional	101432795