




Downlight for enhanced lighting requirements. For illuminating workplaces with special risks, swimming pools or sports facilities. Robust, chlorine-resistant housing made of die-cast aluminium with optional lateral cable gland.



Technical data


| | |
|----------------------------|--------------------|
| Material: | die-cast aluminum |
| Illuminant: | 1 x 12W LED-module |
| Luminous flux: | 1652 lm |
| Nominal voltage AC: | 230V ±10% 50/60 Hz |
| Nominal voltage DC: | 176 - 264 V |
| Nominal current AC: | 84 mA |
| Nominal current DC: | 80 mA |

| | |
|---------------------------|--|
| Apparent power: | 19,4 VA |
| Effective power: | 16,7 W |
| inrush current: | 11 A / 68 µs |
| Protection class: | I |
| Input terminals: | 2.5mm ² feed through wiring |
| Temperature ta: | -15...+40 °C |
| Impact resistance: | IK10 |




Articles

| | | |
|----------------------------|----------------------|---------------------------|
| SN 8500-12 FLD 230V | | |
| Colors | RAL 9006 | RAL (special) |
| Art. no. | 101389854 | 101389955 |
| ceiling mounting | Light colour: 4000 K | Protection category: IP65 |




Ringbolts for SN 8500/24xx Art. no. 100912635

optional




Recessed ceiling frame SN 8500, RAL 9006 Art. no. 101432593

optional



Wall bracket SN 8500, RAL 9006 Art. no. 101432795

optional



| Name | Accessories | Art. no. |
|--|--------------------|-----------------|
| Recessed ceiling frame SN 8500, RAL 9006 | optional | 101432593 |
| Ringbolts for SN 8500/24xx | optional | 100912635 |
| Wall bracket SN 8500, RAL 9006 | optional | 101432795 |