

230V**SN 8500-12 Downlights****J/SV**

For connection to JOKER-central battery systems




Downlight for enhanced lighting requirements. For illuminating work-places with special risks, swimming pools or sports facilities. Robust, chlorine-resistant housing made of die-cast aluminium with optional lateral cable gland.

**Technical data**


Material:	die-cast aluminum
Illuminant:	1 x 12W LED-module
Luminous flux:	1652 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	84 mA
Nominal current DC:	80 mA

Apparent power:	19,4 VA
Effective power:	17,9 W
Inrush current:	11 A / 264 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10


**Articles****SN 8500 -12 LED J/SV/S**

Colors	HWF 9006	HWF (special)
Art. no.	101302655	101302756


ceiling mounting Light colour: 4000 K Protection category: IP65

**Ringbolts for SN 8500/24xx**


Art. no. 100912635

**Recessed ceiling frame SN 8500, HWF 9006**

Art. no. 101432593

**Wall bracket SN 8500, RAL 9006**

Art. no. 101432795



Subject to technical changes! Due to component tolerances measured values may vary!

www.inotec-licht.de



2023.10.21

Name	Accessories	Art. no.
Haube SN 8500	Ersatzteil	50207
LM 18x18 1/4K PADS	Ersatzteil	104440203
Recessed ceiling frame SN 8500, HWF 9006	optional	101432593
Recessed ceiling frame SN 8500, HWF SC		101432492
Ringbolts for SN 8500/24xx	optional	100912635
Wall bracket SN 8500, RAL 9006	optional	101432795