




Downlight for enhanced lighting requirements. For illuminating workplaces with special risks, swimming pools or sports facilities. Robust, chlorine-resistant housing made of die-cast aluminium with optional lateral cable gland.



Technical data


Material:	die-cast aluminum
Illuminant:	1 x 25W LED-module
Luminous flux:	3401 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	134 mA
Nominal current DC:	135 mA

Apparent power:	30,9 VA
Effective power:	28,4 W
inrush current:	11 A / 68 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10




Articles

SN 8500-25 FLD 230V		
Colors	RAL 9006	RAL (special)
Art. no.	101390056	101390157
ceiling mounting	Light colour: 4000 K	Protection category: IP65




Ringbolts for SN 8500/24xx Art. no. 100912635

optional




Recessed ceiling frame SN 8500, RAL 9006 Art. no. 101432593

optional



Wall bracket SN 8500, RAL 9006 Art. no. 101432795

optional



Name	Accessories	Art. no.
Recessed ceiling frame SN 8500, RAL 9006	optional	101432593
Ringbolts for SN 8500/24xx	optional	100912635
Wall bracket SN 8500, RAL 9006	optional	101432795