




Downlight for enhanced lighting requirements. For illuminating work-places with special risks, swimming pools or sports facilities. Robust, chlorine-resistant housing made of die-cast aluminium with optional lateral cable gland.



Technical data

Material:	die-cast aluminum
Illuminant:	1 x 25W LED-module
Luminous flux:	3401 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	134 mA
Nominal current DC:	135 mA

Apparent power:	30,9 VA
Effective power:	29,8 W
Inrush current:	11 A / 264 µs
Protection class:	I
Input terminals:	2.5mm² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10




Articles

SN 8500 -25 LED J/SV/S

Colors	HWF 9006	HWF (special)
Art. no.	101302857	101302958

ceiling mounting Light colour: 4000 K Protection category: IP65




Ringbolts for SN 8500/24xx

Art. no. 100912635




Recessed ceiling frame SN 8500, HWF 9006

Art. no. 101432593



Wall bracket SN 8500, RAL 9006

Art. no. 101432795



Name	Accessories	Art. no.
Haube SN 8500	spare part	50207
LED driver replacement SN 8500-25	spare part	101484026
LM 24x24 1/4K PADS LED Modul	spare part	104440304
M20 cable glands (PU 2 pcs.)	optional	104661784
Recessed ceiling frame SN 8500, HWF 9006	optional	101432593
Ringbolts for SN 8500/24xx	optional	100912635
Wall bracket SN 8500, RAL 9006	optional	101432795