

230V**SN 8500-25 T/S Downlights****J/SV**

for connection to JOKER-central battery systems




Downlight for enhanced lighting requirements. For illuminating workplaces with special risks, swimming pools or sports facilities. Robust, chlorine-resistant housing made of die-cast aluminium with optional lateral cable gland. Including timer function to switch off or dim luminaires in battery mode to reduce the required lighting level (acc. to EN 12193) or in buildings with different rated duration times.

**Technical data**


Material:	die-cast aluminum
Illuminant:	1 x 25W LED-module
Luminous flux:	3401 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	134 mA
Nominal current DC:	135 mA

Apparent power:	30,9 VA
Effective power:	29,8 W
Inrush current:	15 A / 82 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10

**Articles****SN 8500 -25 LED J/SV T/S**

Colors	HWF 9006	HWF (special)
Art. no.	101303059	101303160


ceiling mounting Light colour: 4000 K Protection category: IP65

**Ringbolts for SN 8500/24xx**


Art. no. 100912635

**Recessed ceiling frame SN 8500, HWF 9006**

Art. no. 101432593

**Wall bracket SN 8500, RAL 9006**

Art. no. 101432795



Name	Accessories	Art. no.
Haube SN 8500	Ersatzteil	50207
LED driver replacement SN 8500-25	Ersatzteil	101484026
LM 24x24 1/4K PADS	Ersatzteil	104440304
Recessed ceiling frame SN 8500, HWF 9006	optional	101432593
Ringbolts for SN 8500/24xx	optional	100912635
Wall bracket SN 8500, RAL 9006	optional	101432795