




LED emergency luminaire with optimized light distribution for illuminating areas with high mounting heights. LED device carrier for XAL MOVE IT PRO with locking function of the circuit selector switch.

Technical data

Illuminant:	1 x 3,5W LED-module	Effective power:	5,1 W
Luminous flux:	498 lm	Protection class:	III
Nominal voltage DC:	24 V $\pm$ 25 %	Input terminals:	2.5mm ² feed through wiring
Nominal current DC:	210 mA	Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

2.5m	5.4m	12.8m
3.0	5.8	13.8
4.0	6.3	15.5
5.0	6.4	16.7
6.0	6.2	17.7
7.0	5.8	18.1
8.0	4.7	17.9
9.0	4.4	17.9

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

2.5m	3.3m	8.1m
3.0	3.7	9.6
4.0	4.3	11.0
5.0	4.5	13.2
6.0	4.5	14.6
7.0	4.3	15.7
8.0	3.9	16.5
9.0	3.1	17.2

Articles

SN 9024.1 MOVE IT PRO -12 SHB LED 24V		
Colors	RAL 9005	RAL 9016
Art. no.	104906106	104980773

zum Einbau in XAL Lichtband-Light colour: 4000 K Protection category: IP20

Name	Accessories	Art. no.
ILD 24/4-CC-320-L Mini	spare part	104757370
LM 24x21 1(12V)/4K KB300 LED Modul	spare part	104828506

