SN 9024.1 MOVE IT PRO-12 SHB Lichtbandleuchten

For connection to JOKER-central battery systems

INOTEC Sicherheitstechnik GmbH

LED emergency luminaire with optimized light distribution for illuminating areas with high mounting heights.LED device carrier for XAL MOVE IT PRO with locking function of the circuit selector switch.

Technical data

Illuminant:	1 x 3,5W LED-module
Luminous flux:	498 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	31 mA
Nominal current DC:	26 mA

Apparent power:	7,2 VA
Effective power:	6,0 W
Inrush current:	6 A / 98 µs
Protection class:	I
Input terminals:	2.5mm² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

2.5	5.4	12.8
3.0	5.8	13.8
4.0	6.3	15.5
5.0	6.4	16.7
6.0	6.2	17.7
7.0	5.8	18.1
8.0	4.7	17.9
9.0	4.4	17.9

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

2.5	3.3	8.1
3.0	3.7	9.6
4.0	4.3	11.0
5.0	4.5	13.2
6.0	4.5	14.6
7.0	4.3	15.7
8.0	3.9	16.5
9.0	3.1	17.2

Articles

SN 9024.1 MOVE IT PRO -12 SHB LED J/SV		
Colors	RAL 9005	RAL 9016
Art. no.	104905601	104980571

zum Einbau in XAL Lichtband-system MOVE IT PRO

Light colour: 4000 K

Protection category: IP20

Name	Accessories	Art. no.
J-ET 5.1 SV-max. 24V DC320mA const.	spare part	101422893
LM 24x21 1(12V)/4K KB300 LED Modul	spare part	104828506