




Elegant LED downlight for recessed ceiling mounting or luminaire integration with anodised aluminium cover without any visible screws. Ideal for area or escape route illumination.

Technical data

Material:	aluminium powder-coated	Nominal current DC:	80 mA
Illuminant:	1 x 1W LED-module	Protection class:	III
Luminous flux:	70 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance (m)	1.0lx	1.5lx	2.0lx
2.5	2.1	5.9	
3.0	2.0	6.0	
3.5	1.8	6.1	
4.0	1.5	5.9	


Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Distance (m)	1.0lx	1.5lx	2.0lx
2.5	1.5	5.2	
3.0	1.5	5.5	
3.5	1.5	5.5	
4.0	1.5	5.5	

Articles


SN 9024 E LED 24V round

Colors	RAL (special)	RAL 7015	RAL 9016	RAL 9016	RAL (special)
Art. no.	101438758	101438657	101438354	101438556	101438455
recessed ceiling mounting	Light colour: 6500 K		Protection category: IP20		



SN 9024 E LED 24V square

Colors	RAL (special)	RAL 7015	RAL 9016	RAL 9016	RAL (special)
Art. no.	101438758	101438657	101438354	101438556	101438455
recessed ceiling mounting	Light colour: 6500 K		Protection category: IP20		



Name	Accessories	Art. no.
LED-Supply 24-3 SK III ext. (Metallgehäuse)	required	101435425

