


Elegant LED safety luminaires with powder-coated cover designed for tool-less recessed ceiling installation.

Technical data

Material:	sheet steel powder-coated	Nominal current DC:	200 mA
Illuminant:	4 x 1W LED-module	Protection class:	III
Luminous flux:	310 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter [m]	Beam diameter [m]	Beam diameter [m]
2.5	3.7	8.5
3.0	4.1	9.7
4.0	4.7	11.5
5.0	5.0	12.9
6.0	5.1	13.9
7.0	4.9	14.3
8.0	4.5	14.4
9.0	3.7	14.3
10.0	2.5	13.8


Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Beam diameter [m]	Beam diameter [m]	Beam diameter [m]
2.5	2.7	6.4
3.0	3.1	7.3
4.0	3.6	9.0
5.0	3.7	10.6
6.0	3.7	11.8
7.0	3.6	12.4
8.0	3.4	12.8
9.0	3.1	12.6
10.0	2.6	12.4

Articles


SN 9104.1 -41 LED 24V round

Colors	stainless steel	RAL 9016	RAL (special)
Art. no.	101323065	101322964	101323166
recessed ceiling mounting	Light colour: 6500 K		Protection category: IP20




SN 9104.1 -41 LED 24V square

Colors	stainless steel	RAL 9016	RAL (special)
Art. no.	101323368	101323267	101323469
recessed ceiling mounting	Light colour: 6500 K		Protection category: IP20



LED-Supply 24-3 SK III ext.

Art. no. 101442091



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK II ext.	required	101436536
LED-Supply 230-3 NE-SV SK II ext.	required	101436738
LED-Supply 230-3 SK II ext.	required	101436637
LED-Supply 24-3 S SK II ext.	required	101436233
LED-Supply 24-3 SK III ext.	required	101442091
LED-Supply 24-3 SK III ext.	required	101435425