


Elegant LED safety luminaires with powder-coated cover designed for tool-less recessed ceiling installation.

### Technical data

<b>Material:</b>	sheet steel powder-coated
<b>Illuminant:</b>	4 x 1W LED-module
<b>Luminous flux:</b>	310 lm
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	36 mA

<b>Nominal current DC:</b>	32 mA
<b>Apparent power:</b>	8,3 VA
<b>Inrush current:</b>	8 A / 50 µs
<b>Protection class:</b>	II
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	2.5	3.7	8.5
2.5	3.7	8.5	
3.0	4.1	9.7	
4.0	4.7	11.5	
5.0	5.0	12.9	
6.0	5.1	13.9	
7.0	4.9	14.3	
8.0	4.5	14.4	
9.0	3.7	14.3	
10.0	2.5	13.8	


Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

[m]	2.5	2.7	6.4
2.5	2.7	6.4	
3.0	3.1	7.3	
4.0	3.6	9.0	
5.0	3.7	10.6	
6.0	3.7	11.8	
7.0	3.6	12.4	
8.0	3.4	12.8	
9.0	3.1	12.6	
10.0	2.6	12.4	

### Articles


#### SN 9104.1 -41 LED J/SV round

Colors	stainless steel	RAL 9016	RAL (special)
Art. no.	101323065	101322964	101323166
recessed ceiling mounting	Light colour: 6500 K		Protection category: IP20




#### SN 9104.1 -41 LED J/SV square

Colors	stainless steel	RAL 9016	RAL (special)
Art. no.	101323368	101323267	101323469
recessed ceiling mounting	Light colour: 6500 K		Protection category: IP20



#### LED-Supply 230-3 J-SV SK II ext.

Art. no. 101436536



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK II ext.	required	101436536
LED-Supply 230-3 NE-SV SK II ext.	required	101436738
LED-Supply 230-3 SK II ext.	required	101436637
LED-Supply 24-3 S SK II ext.	required	101436233
LED-Supply 24-3 SK III ext.	required	101442091
LED-Supply 24-3 SK III ext.(Metallgehäuse)	required	101435425