


Elegant LED safety luminaires with powder-coated cover designed for tool-less recessed ceiling installation.



**Technical data**

<b>Material:</b>	Sheet steel powder-coated
<b>Illuminant:</b>	LEDs
<b>Luminous flux:</b>	310 lm
<b>Nominal voltage AC:</b>	230V AC ±10% 50/60 Hz
<b>Nominal current:</b>	32 mA

<b>Apparent power:</b>	8,30 VA
<b>Inrush current:</b>	8 A / 50 µs
<b>Protection class:</b>	II
<b>Input terminals:</b>	2,5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C



Minimum illumination 1.0 lx (middle of escape route), Maintenance factor 0.8

[m]	2.5	3.7	8.5
2.5	3.7	8.5	18.8
3.0	4.1	9.7	21.6
4.0	4.7	11.5	25.5
5.0	5.0	12.9	28.4
6.0	5.1	13.9	30.8
7.0	4.9	14.3	31.6
8.0	4.5	14.4	31.7
9.0	3.7	14.3	31.6
10.0	2.5	13.8	30.5

Minimum illumination 1.0 Lux (area illumination), Maintenance factor 0.8


[m]	2.5	2.7	6.4
2.5	2.7	6.4	15.8
3.0	3.1	7.3	18.1
4.0	3.6	9.0	22.5
5.0	3.7	10.6	26.4
6.0	3.7	11.8	29.2
7.0	3.6	12.4	30.8
8.0	3.4	12.8	31.7
9.0	3.1	12.6	31.3
10.0	2.6	12.4	30.5

**Available colours** Add colour code to the article no. e.g. 800 014 LXX

RAL 9016 (Traffic white): **L04**  Special colour: **L99**

**Articles**

**SN 9104.1-41 LED NE/SV round** Art. no. 809 407  
Recessed ceiling mounting Protection category: IP20



**LED-Supply 230-3 NE-SV SK II ext.** Art. no. 890 492  
required accessoire

