




LED safety luminaire with optimised light distribution for the illumination of escape routes. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.

Luminaire IP40 / LED-Supply IP20



Technical data

Material:	die-cast aluminum powder-coated	Nominal current DC:	65 mA
Illuminant:	1 x 0,9W LED-module	Protection class:	III
Luminous flux:	139 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	⊘	⊘	⊘	⊘
2.5	6.8	17.0	5.3	1.9
3.0	5.3	18.1	5.4	1.8
3.5	4.8	17.9	5.4	1.6
4.0	3.8	17.3	5.3	1.3
4.5	3.0	14.3	5.0	0.9

Articles


SN 9400 -03 ALB LED 24V round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060568	101323974	101324075
recessed ceiling mounting	Light colour: 4000 K		Protection category: IP20




SN 9400 -03 ALB LED 24V square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060972	101324782	101324883
recessed ceiling mounting	Light colour: 4000 K		Protection category: IP20



LED-Supply 24-3 SK III ext.

Art. no. 101442091



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK IIext.	required	101436536
LED-Supply 230-3 NE-SV SK IIext.	required	101436738
LED-Supply 24-3 SK III ext.	required	101442091