24V

SN 9400-03 ALB Downlights

For connection to INOTEC systems with 24V circuits

INOTEC Sicherheitstechnik GmbH

LED safety luminaire with optimised light distribution for the illumination of escape routes. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.
Luminaire IP40 / LED-Supply IP20

Technical data

Material:	die-cast aluminum powder-coated	**Nominal current DC:**	65 mA
Illuminant:	1 x 0,9W LED-module	**Protection class:**	III
Luminous flux:	139 lm	**Input terminals:**	2.5mm² feed through wiring
Nominal voltage DC:	24 V ±20 %	**Temperature ta:**	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]				
2.5	6.8	17.0	5.3	1.9
3.0	5.3	18.1	5.4	1.8
3.5	4.8	17.9	5.4	1.6
4.0	3.8	17.3	5.3	1.3
4.5	3.0	14.3	5.0	0.9

Articles

SN 9400 -03 ALB LED 24V round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060568	101323974	101324075

recessed ceiling mounting | Light colour: 4000 K | Protection category: IP20



SN 9400 -03 ALB LED 24V square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060972	101324782	101324883

recessed ceiling mounting | Light colour: 4000 K | Protection category: IP20



LED-Supply 24-3 SK III ext.

Art. no. 101442091



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK IIext.	required	101436536
LED-Supply 230-3 NE-SV SK IIext.	required	101436738
LED-Supply 24-3 SK III ext.	required	101442091