




LED safety luminaire with optimised light distribution for the illumination of escape routes. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.

Luminaire IP40 / LED-Supply IP20

Technical data

Material:	die-cast aluminum powder-coated	Apparent power:	3,5 VA
Illuminant:	1 x 0,9W LED-module	Inrush current:	8 A / 50 µs
Luminous flux:	139 lm	Protection class:	II
Nominal voltage AC:	230V AC ±10% 50/60 Hz	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	15 mA	Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


	2.5	3.0	3.5	4.0	4.5
6.8	6.8	5.3	4.8	3.8	3.0
17.0	17.0	18.1	17.9	17.3	14.3
5.3	5.3	5.4	5.4	5.3	5.0
1.9	1.9	1.8	1.6	1.3	0.9

Articles

SN 9400-03 ALB LED NE/SV round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060568	101323974	101324075


recessed ceiling mounting Light colour: 4000 K Protection category: IP20



SN 9400-03 ALB LED NE/SV square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060972	101324782	101324883


recessed ceiling mounting Light colour: 4000 K Protection category: IP20



LED-Supply 230-3 NE-SV SK II ext.

Art. no. 101436738

required



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK II ext.	required	101436536
LED-Supply 230-3 NE-SV SK II ext.	required	101436738
LED-Supply 24-3 SK III ext.	required	101442091