




LED safety luminaire with optimised light distribution for the illumination of small areas such as lavatories or electrical operating rooms with a luminaire. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 0,9W LED-module
Luminous flux:	146 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	13 mA
Nominal current DC:	12 mA

Apparent power:	3,0 VA
Effective power:	2,6 W
Inrush current:	6 A / 22 µs
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

2.5	3.3	8.2
3.0	3.5	8.8
3.5	3.6	9.4
4.0	3.5	9.8
4.5	3.2	10.0
5.0	2.7	10.1



Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

2.5	2.2	6.8
3.0	2.3	7.4
3.5	2.5	8.0
4.0	2.6	8.4
4.5	2.5	8.6
5.0	2.4	8.2

Articles

SN 9400 -03 SLB FLD 230V round			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102061174	101325186	101325287
recessed ceiling mounting	Light colour: 4000 K		Protection category: IP20

SN 9400 -03 SLB FLD 230V square			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102061376	101325590	101325691
recessed ceiling mounting	Light colour: 4000 K		Protection category: IP20



FLD-Supply 230/320 SK II ext.	Art. no. 101445226
--------------------------------------	--------------------

Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK IIext.	required	101436536
LED-Supply 230-3 NE-SV SK IIext.	required	101436738
LED-Supply 230-3 SK II ext.	required	101436637
LED-Supply 24-3 SK III ext.	required	101442091

