





LED safety luminaire with optimised light distribution for the illumination of escape routes with high mounting heights. Also suitable for illumination of firefighting and fire alarm systems as well as first aid stations with 5 lx vertical illuminance. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 1,8W LED-module
Luminous flux:	287 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	19 mA
Nominal current DC:	16 mA

Apparent power:	4,4 VA
Effective power:	3,6 W
Inrush current:	8 A / 50 µs
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Mounting height (m)	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0
5.0	6.5	16.0	5.8	1.9				
6.0	7.0	17.2	5.2	2.1				
7.0	7.3	18.4	5.5	2.3				
8.0	7.3	19.5	5.8	2.4				
9.0	6.8	20.3	6.2	2.4				
10.0	6.0	20.7	6.5	2.4				
11.0	5.4	20.7	6.7	2.2				
12.0	4.2	20.0	6.8	0.7				

Articles


SN 9400-06 AHB LED J/SV round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060669	101324176	101324277
recessed ceiling mounting	Light colour: 4000 K		Protection category: IP20




SN 9400-06 AHB LED J/SV square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102061073	101324984	101325085
recessed ceiling mounting	Light colour: 4000 K		Protection category: IP20



LED-Supply 230-3 J-SV SK IIext.

Art. no. 101436536



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK IIext.	required	101436536
LED-Supply 230-3 NE-SV SK IIext.	required	101436738
LED-Supply 24-3 SK III ext.	required	101442091