




LED safety luminaire with optimised light distribution for the illumination of escape routes. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 1,8W LED-module
Luminous flux:	281 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	17 mA
Nominal current DC:	16 mA

Apparent power:	3,9 VA
Effective power:	3,6 W
Inrush current:	6 A / 22 µs
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Beam diameter (m)	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5
Beam diameter (m)	7.8	8.4	8.6	6.8	6.7	6.5	5.7	5.0	4.3
Beam diameter (m)	19.1	20.8	22.0	23.3	22.6	22.3	19.2	19.1	19.0
Beam diameter (m)	7.1	7.4	7.6	7.7	7.8	7.7	7.6	7.5	7.2
Beam diameter (m)	2.7	2.7	2.7	2.7	2.6	2.4	2.1	1.8	1.3

Articles

SN 9400 -06 ALB FLD 230V round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102061275	101325388	101325489


recessed ceiling mounting Light colour: 4000 K Protection category: IP20



SN 9400 -06 ALB FLD 230V square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102061477	101325792	101325893


recessed ceiling mounting Light colour: 4000 K Protection category: IP20



FLD-Supply 230/320 SK II ext.

Art. no. 101445226

required



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK II ext.	required	101436536
LED-Supply 230-3 NE-SV SK II ext.	required	101436738
LED-Supply 230-3 SK II ext.	required	101436637
LED-Supply 24-3 SK III ext.	required	101442091
LM 39x39 1(6V)/4K KB250 LED Modul	spare part	104556300