




LED safety luminaire with optimised light distribution for the illumination of escape routes. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.



### Technical data

|                            |                                 |                          |                                        |
|----------------------------|---------------------------------|--------------------------|----------------------------------------|
| <b>Material:</b>           | die-cast aluminum powder-coated | <b>Effective power:</b>  | 2,7 W                                  |
| <b>Illuminant:</b>         | 1 x 1,8W LED-module             | <b>Protection class:</b> | III                                    |
| <b>Luminous flux:</b>      | 281 lm                          | <b>Input terminals:</b>  | 2.5mm <sup>2</sup> feed through wiring |
| <b>Nominal voltage DC:</b> | 24 V ±20 %                      | <b>Temperature ta:</b>   | -15...+40 °C                           |
| <b>Nominal current DC:</b> | 110 mA                          |                          |                                        |




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

|      | 2.5  | 3.0  | 3.5  | 4.0  | 4.5  | 5.0  | 5.5  | 6.0  | 6.5 |
|------|------|------|------|------|------|------|------|------|-----|
| 7.8  | 8.4  | 8.6  | 6.8  | 6.7  | 6.5  | 5.7  | 5.0  | 4.3  |     |
| 19.1 | 20.8 | 22.0 | 23.3 | 22.6 | 22.3 | 19.2 | 19.1 | 19.0 |     |
| 7.1  | 7.4  | 7.6  | 7.7  | 7.8  | 7.7  | 7.6  | 7.5  | 7.2  |     |
| 2.7  | 2.7  | 2.7  | 2.7  | 2.6  | 2.4  | 2.1  | 1.8  | 1.3  |     |

### Articles


#### SN 9400 -06 ALB LED 24V round

| Colors                    | RAL 9005             | RAL 9016                  | RAL (special) |
|---------------------------|----------------------|---------------------------|---------------|
| Art. no.                  | 102061275            | 101325388                 | 101325489     |
| recessed ceiling mounting | Light colour: 4000 K | Protection category: IP20 |               |



#### SN 9400 -06 ALB LED 24V square


| Colors                    | RAL 9005             | RAL 9016                  | RAL (special) |
|---------------------------|----------------------|---------------------------|---------------|
| Art. no.                  | 102061477            | 101325792                 | 101325893     |
| recessed ceiling mounting | Light colour: 4000 K | Protection category: IP20 |               |



#### LED-Supply 24-3 SK III ext.

Art. no. 101442091

required



| Name                              | Accessories | Art. no.  |
|-----------------------------------|-------------|-----------|
| FLD-Supply 230/320 SK II ext.     | required    | 101445226 |
| LED-Supply 230-3 J-SV SK II ext.  | required    | 101436536 |
| LED-Supply 230-3 NE-SV SK II ext. | required    | 101436738 |
| LED-Supply 230-3 SK II ext.       | required    | 101436637 |
| LED-Supply 24-3 SK III ext.       | required    | 101442091 |
| LM 39x39 1(6V)/4K KB250 LED Modul | spare part  | 104556300 |