




LED safety luminaire with optimised light distribution for the illumination of escape routes. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.

Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 1,8W LED-module
Luminous flux:	281 lm
Nominal voltage AC:	230V AC ±10% 50/60 Hz
Nominal current AC:	19 mA

Apparent power:	4,4 VA
Inrush current:	8 A / 50 µs
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


[m]	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5
7.8	7.8	8.4	8.6	6.8	6.7	6.5	5.7	5.0	4.3
19.1	19.1	20.8	22.0	23.3	22.6	22.3	19.2	19.1	19.0
7.1	7.1	7.4	7.6	7.7	7.8	7.7	7.6	7.5	7.2
2.7	2.7	2.7	2.7	2.7	2.6	2.4	2.1	1.8	1.3

Articles

SN 9400-06 ALB LED NE/SV round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102061275	101325388	101325489


recessed ceiling mounting Light colour: 4000 K Protection category: IP20



SN 9400-06 ALB LED NE/SV square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102061477	101325792	101325893


recessed ceiling mounting Light colour: 4000 K Protection category: IP20



LED-Supply 230-3 NE-SV SK II ext.

Art. no. 101436738

required



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK II ext.	required	101436536
LED-Supply 230-3 NE-SV SK II ext.	required	101436738
LED-Supply 230-3 SK II ext.	required	101436637
LED-Supply 24-3 SK III ext.	required	101442091