





LED safety luminaire with optimised light distribution for the illumination of areas with high mounting heights. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 3,5W LED-module
Luminous flux:	545 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	33 mA
Nominal current DC:	25 mA

Apparent power:	7,6 VA
Effective power:	5,7 W
Inrush current:	8 A / 50 µs
Protection class:	II
Input terminals:	2.5mm² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

6.0	6.9	17.5
6.5	7.0	18.1
7.0	7.1	18.6
7.5	7.1	19.0
8.0	6.9	19.3
8.5	6.7	19.6
9.0	6.3	19.8
9.5	5.8	20.0
10.0	5.2	20.1

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


6.0	4.9	14.2
6.5	5.1	14.7
7.0	5.0	14.9
7.5	4.9	16.2
8.0	4.7	16.3
8.5	4.7	16.8
9.0	4.6	17.5
9.5	4.5	17.7
10.0	4.3	16.6

Articles

SN 9400 -12 SHB LED J/SV round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060467	101323772	101323873


recessed ceiling mounting Light colour: 4000 K Protection category: IP20



SN 9400 -12 SHB LED J/SV square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060871	101324580	101324681


recessed ceiling mounting Light colour: 4000 K Protection category: IP20



LED-Supply 230-3 J-SV SK IIext.

Art. no. 101436536

required



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK IIext.	required	101436536
LED-Supply 230-3 NE-SV SK IIext.	required	101436738
LED-Supply 24-3 SK III ext.	required	101442091
LM 39x39 1(12V)/4K KB250 LED Modul	spare part	104556195