




LED safety luminaire with optimised light distribution for the illumination of areas with high mounting heights. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.

Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 3,5W LED-module
Luminous flux:	545 lm
Nominal voltage AC:	230V AC ±10% 50/60 Hz
Nominal current AC:	33 mA

Apparent power:	7,6 VA
Inrush current:	8 A / 50 µs
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	6.0	6.9	17.5
6.5	6.5	7.0	18.1
7.0	7.0	7.1	18.6
7.5	7.1	7.1	19.0
8.0	6.9	6.9	19.3
8.5	6.7	6.7	19.6
9.0	6.3	6.3	19.8
9.5	5.8	5.8	20.0
10.0	5.2	5.2	20.1

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


[m]	6.0	4.9	14.2
6.5	6.5	5.1	14.7
7.0	7.0	5.0	14.9
7.5	7.5	4.9	16.2
8.0	8.0	4.7	16.3
8.5	8.5	4.7	16.8
9.0	9.0	4.6	17.5
9.5	9.5	4.5	17.7
10.0	10.0	4.3	16.6

Articles

SN 9400-12 SHB LED NE/SV round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060467	101323772	101323873


recessed ceiling mounting Light colour: 4000 K Protection category: IP20



SN 9400-12 SHB LED NE/SV square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060871	101324580	101324681


recessed ceiling mounting Light colour: 4000 K Protection category: IP20



LED-Supply 230-3 NE-SV SK II ext.

Art. no. 101436738

required



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK II ext.	required	101436536
LED-Supply 230-3 NE-SV SK II ext.	required	101436738
LED-Supply 24-3 SK III ext.	required	101442091