




LED safety luminaire with optimised light distribution for the illumination of areas. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 3,5W LED-module
Luminous flux:	517 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	25 mA
Nominal current DC:	25 mA

Apparent power:	5,8 VA
Effective power:	5,5 W
Inrush current:	6 A / 22 µs
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Height [m]	Beam diameter [m]	Beam diameter [m]
2.5	5.9	15.2
3.0	5.9	16.3
3.5	5.9	16.7
4.0	5.8	16.9
4.5	5.6	16.8
5.0	5.0	16.7
5.5	3.8	16.4
6.0	1.4	16.2

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


Height [m]	Beam diameter [m]	Beam diameter [m]
2.5	4.5	12.6
3.0	4.9	14.0
3.5	5.0	14.9
4.0	4.6	15.5
4.5	4.1	15.1
5.0	3.9	14.5
5.5	3.7	14.3
6.0	3.5	14.1

Articles


SN 9400 -12 SLB FLD 230V round			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060366	101323570	101323671
recessed ceiling mounting	Light colour: 4000 K		Protection category: IP20



SN 9400 -12 SLB FLD 230V square			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060770	101324378	101324479
recessed ceiling mounting	Light colour: 4000 K		Protection category: IP20



FLD-Supply 230/320 SK II ext.	Art. no. 101445226
--------------------------------------	--------------------



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK IIext.	required	101436536
LED-Supply 230-3 NE-SV SK IIext.	required	101436738
LED-Supply 230-3 SK II ext.	required	101436637
LED-Supply 24-3 SK III ext.	required	101442091

