24V **SN 9400-12 SLB** Downlights

For connection to INOTEC systems with 24V circuits

INOTEC Sicherheitstechnik GmbH

LED safety luminaire with optimised light distribution for the illumination of areas. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.

IP20

IP43

Technical data

Material:	die-cast aluminum powder-coated	**Nominal current DC:**	185 mA
Illuminant:	1 x 3,5W LED-module	**Protection class:**	III
Luminous flux:	517 lm	**Input terminals:**	2.5mm² feed through wiring
Nominal voltage DC:	24 V ±20 %	**Temperature ta:**	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]		
2.5	5.9	15.2
3.0	5.9	16.3
3.5	5.9	16.7
4.0	5.8	16.9
4.5	5.6	16.8
5.0	5.0	16.7
5.5	3.8	16.4
6.0	1.4	16.2

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

[m]		
2.5	4.5	12.6
3.0	4.9	14.0
3.5	5.0	14.9
4.0	4.6	15.5
4.5	4.1	15.1
5.0	3.9	14.5
5.5	3.7	14.3
6.0	3.5	14.1

Articles

SN 9400 -12 SLB LED 24V round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060366	101323570	101323671

recessed ceiling mounting — Light colour: 4000 K — Protection category: IP20



SN 9400 -12 SLB LED 24V square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060770	101324378	101324479

recessed ceiling mounting — Light colour: 4000 K — Protection category: IP20



LED-Supply 24-3 SK III ext. — Art. no. 101442091



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK IIext.	required	101436536
LED-Supply 230-3 NE-SV SK IIext.	required	101436738
LED-Supply 230-3 SK II ext.	required	101436637
LED-Supply 24-3 SK III ext.	required	101442091