




LED safety luminaire with optimised light distribution for the illumination of areas. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 3,5W LED-module
Luminous flux:	517 lm
Nominal voltage DC:	24 V ±20 %
Nominal current DC:	185 mA

Effective power:	4,5 W
Protection class:	III
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0
2.5	5.9	5.9	5.9	5.8	5.6	5.0	3.8	1.4
3.0	15.2	16.3	16.7	16.9	16.8	16.7	16.4	16.2


Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

[m]	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0
2.5	12.6	14.0	14.9	15.5	15.1	14.5	14.3	14.1
3.0	14.0	14.9	15.5	15.1	14.5	14.3	14.1	14.1

Articles


SN 9400 -12 SLB LED 24V round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060366	101323570	101323671
recessed ceiling mounting	Light colour: 4000 K	Protection category: IP20	



SN 9400 -12 SLB LED 24V square


Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060770	101324378	101324479
recessed ceiling mounting	Light colour: 4000 K	Protection category: IP20	



LED-Supply 24-3 SK III ext.

Art. no. 101442091

required



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK II ext.	required	101436536
LED-Supply 230-3 NE-SV SK II ext.	required	101436738
LED-Supply 230-3 SK II ext.	required	101436637
LED-Supply 24-3 SK III ext.	required	101442091
LM 39x39 1(12V)/4K KB250 LED Modul	spare part	104556195