




LED safety luminaire with optimised light distribution for the illumination of areas. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 3,5W LED-module
Luminous flux:	517 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	33 mA
Nominal current DC:	25 mA

Apparent power:	7,6 VA
Effective power:	5,7 W
Inrush current:	8 A / 50 µs
Protection class:	II
Input terminals:	2.5mm² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance [m]	2.5	5.9	15.2
2.5	3.0	5.9	16.3
3.5	5.9	16.7	
4.0	5.8	16.9	
4.5	5.6	16.8	
5.0	5.0	16.7	
5.5	3.8	16.4	
6.0	1.4	16.2	

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


Distance [m]	2.5	4.5	12.6
2.5	3.0	4.9	14.0
3.5	5.0	14.9	
4.0	4.6	15.5	
4.5	4.1	15.1	
5.0	3.9	14.5	
5.5	3.7	14.3	
6.0	3.5	14.1	

Articles

SN 9400 -12 SLB LED J/SV round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060366	101323570	101323671


recessed ceiling mounting Light colour: 4000 K Protection category: IP20



SN 9400 -12 SLB LED J/SV square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102060770	101324378	101324479


recessed ceiling mounting Light colour: 4000 K Protection category: IP20



LED-Supply 230-3 J-SV SK II ext.

Art. no. 101436536

required



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK II ext.	required	101436536
LED-Supply 230-3 NE-SV SK II ext.	required	101436738
LED-Supply 230-3 SK II ext.	required	101436637
LED-Supply 24-3 SK III ext.	required	101442091
LM 39x39 1(12V)/4K KB250 LED Modul	spare part	104556195