





LED safety luminaire with optimised light distribution for the illumination of escape routes. Recessed ceiling luminaires with powder-coated aluminium trim without visible screws. For installation in Ø 68mm socket. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated	Effective power:	1,7 W
Illuminant:	1 x 0,9W LED-module	Protection class:	III
Luminous flux:	139 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C
Nominal current DC:	70 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Beam diameter [m]	2.5	3.0	3.5	4.0	4.5
6.8	6.8	5.3	4.8	3.8	3.0
17.0	17.0	18.1	17.9	17.3	14.3
5.3	5.3	5.4	5.4	5.3	5.0
1.9	1.8	1.6	1.3	0.9	

Articles

SN 9424 -03 ALB LED 24V round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102064511	101359744	101359845


switch box installation Light colour: 4000 K Protection category: IP20



SN 9424 -03 ALB LED 24V square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102064915	101360552	101360653

switch box installation Light colour: 4000 K Protection category: IP20



Name	Accessories	Art. no.
ILD 24/4-CC-320-C	spare part	101425321
LM 39x39 1(3V)/4K KB150 24V LED Modul	spare part	104593379