





LED safety luminaire with optimised light distribution for the illumination of escape routes with high mounting heights. Also suitable for illumination of firefighting and fire alarm systems as well as first aid stations with 5 lx vertical illuminance.

Recessed ceiling luminaires with powder-coated aluminium trim without visible screws. For installation in Ø 68mm socket. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated	Effective power:	2,8 W
Illuminant:	1 x 1,8W LED-module	Protection class:	III
Luminous flux:	287 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C
Nominal current DC:	115 mA		




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Height [m]	1	2	3	4	5
5.0	6.5	16.0	5.8	1.9	
6.0	7.0	17.2	5.2	2.1	
7.0	7.3	18.4	5.5	2.3	
8.0	7.3	19.5	5.8	2.4	
9.0	6.8	20.3	6.2	2.4	
10.0	6.0	20.7	6.5	2.4	
11.0	5.4	20.7	6.7	2.2	
12.0	4.2	20.0	6.8	0.7	

Articles


SN 9424 -06 AHB LED 24V round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102064612	101359946	101360047
switch box installation		Light colour: 4000 K	Protection category: IP20



SN 9424 -06 AHB LED 24V square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102065016	101360754	101360855
switch box installation		Light colour: 4000 K	Protection category: IP20



Name	Accessories	Art. no.
ILD 24/4-CC-320-C	spare part	101425321
LM 39x39 1(6V)/4K KB150 LED Modul	spare part	104556704