





LED safety luminaire with optimised light distribution for the illumination of escape routes with high mounting heights. Also suitable for illumination of firefighting and fire alarm systems as well as first aid stations with 5 lx vertical illuminance.

Recessed ceiling luminaires with powder-coated aluminium trim without visible screws. For installation in Ø 68mm socket. Incl. 4-chip LED illuminant for maximum safety.



### Technical data

<b>Material:</b>	die-cast aluminum powder-coated	<b>Nominal current DC:</b>	110 mA
<b>Illuminant:</b>	1 x 1,8W LED-module	<b>Protection class:</b>	III
<b>Luminous flux:</b>	287 lm	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal voltage DC:</b>	24 V ±20 %	<b>Temperature ta:</b>	-15...+40 °C




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	5.0	6.5	16.0	5.8	1.9
5.0	6.5	16.0	5.8	1.9	
6.0	7.0	17.2	5.2	2.1	
7.0	7.3	18.4	5.5	2.3	
8.0	7.3	19.5	5.8	2.4	
9.0	6.8	20.3	6.2	2.4	
10.0	6.0	20.7	6.5	2.4	
11.0	5.4	20.7	6.7	2.2	
12.0	4.2	20.0	6.8	0.7	

### Articles

#### SN 9424 -06 AHB LED 24V round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102064612	101359946	101360047
switch box installation	Light colour: 4000 K		Protection category: IP20



#### SN 9424 -06 AHB LED 24V square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102065016	101360754	101360855
switch box installation	Light colour: 4000 K		Protection category: IP20

