





LED safety luminaire with optimised light distribution for the illumination of areas. Recessed ceiling luminaires with powder-coated aluminium trim without visible screws. For installation in Ø 68mm socket. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 2,1W LED-module
Luminous flux:	322 lm
Nominal voltage DC:	24 V ±25 %
Nominal current DC:	125 mA

Effective power:	3,0 W
Protection class:	III
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Ø [m]	2.5	5.9	15.2
2.5	5.9	16.3	
3.0	5.9	16.7	
3.5	5.8	16.8	
4.0	5.6	16.7	
4.5	5.0	16.4	
5.0	3.8	16.2	
5.5	1.4		

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


Ø [m]	2.5	4.5	12.6
2.5	4.9	14.0	
3.0	5.0	14.9	
3.5	4.6	15.5	
4.0	4.1	15.1	
4.5	3.9	14.5	
5.0	3.7	14.3	
5.5	3.5	14.1	

Articles

SN 9424 -12 SLB LED 24V round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102064309	101359340	101359441


switch box installation Light colour: 4000 K Protection category: IP20



SN 9424 -12 SLB LED 24V square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102064713	101360148	101360249

switch box installation Light colour: 4000 K Protection category: IP20



Name	Accessories	Art. no.
ILD 24/4-CC-200-C	spare part	101425119
LM 39x39 1(12V)/4K KB150 LED Modul	spare part	104556401