




LED safety luminaire with optimised light distribution for the illumination of areas. Recessed ceiling luminaires with powder-coated aluminium trim without visible screws. For installation in Ø 68mm socket. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated	Nominal current DC:	120 mA
Illuminant:	1 x 2,1W LED-module	Protection class:	III
Luminous flux:	322 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter (m)	Beam diameter (m)	Beam diameter (m)
2.5	4.7	12.9
3.0	4.6	13.2
3.5	4.4	13.3
4.0	3.8	13.2
4.5	2.4	12.8


Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Beam diameter (m)	Beam diameter (m)	Beam diameter (m)
2.5	3.7	11.7
3.0	3.7	12.3
3.5	3.2	12.8
4.0	2.9	12.3
4.5	2.6	12.3
5.0	2.4	12.3
5.5	2.2	10.8
6.0	2.0	9.9

Articles

SN 9424 -12 SLB LED 24V round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102064309	101359340	101359441
switch box installation	Light colour: 4000 K		Protection category: IP20



SN 9424 -12 SLB LED 24V square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102064713	101360148	101360249
switch box installation	Light colour: 4000 K		Protection category: IP20

