

230V**SN LINE E-03 ALB Downlights**

For connection to FUSION central battery- or emergency power (NEA) systems




LED safety luminaire with optimised light distribution for the illumination of escape routes. LED carrier for Trilux E-Line trunking system 7650...7LV + 5LV with stainless steel snap locks that can be applied tool-free. Automatic electrical connection by a plug-in contact with circuit selection. Incl. 4-chip LED illuminant for maximum safety.

**Technical data**

Material:	sheet steel painted
Illuminant:	1 x 0,9W LED-module
Luminous flux:	139 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	13 mA
Nominal current DC:	12 mA

Apparent power:	3,0 VA
Effective power:	2,6 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter (mm)	Beam diameter (mm)	Beam diameter (mm)	Beam diameter (mm)	Beam diameter (mm)
2.5	6.8	17.0	5.3	1.9
3.0	5.3	18.1	5.4	1.8
3.5	4.8	17.9	5.4	1.6
4.0	3.8	17.3	5.3	1.3
4.5	3.0	14.3	5.0	0.9

Articles

SN LINE E -03 ALB FLD 230V	
Colors	RAL 9016
Art. no.	101396928

Name	Accessories	Art. no.
FLD 230/4 - CC - 320 - L	Ersatzteil	101965083

07650...7LV+5LV Trilux Light colour: 4000 K Protection category: IP20
E-Line

