




LED safety luminaire with optimised light distribution for the illumination of escape routes. LED carrier for Trilux E-Line trunking system 7650...7LV + 5LV with stainless steel snap locks that can be applied tool-free. Automatic electrical connection by a plug-in contact with circuit selection. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	sheet steel painted	Nominal current DC:	65 mA
Illuminant:	1 x 0,9W LED-module	Protection class:	I
Luminous flux:	139 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance [m]	Ø	Ø	Ø	Ø
2.5	6.8	17.0	5.3	1.9
3.0	5.3	18.1	5.4	1.8
3.5	4.8	17.9	5.4	1.6
4.0	3.8	17.3	5.3	1.3
4.5	3.0	14.3	5.0	0.9

Articles

SN LINE E -03 ALB LED 24V

Colors: RAL 9016
 Art. no.: 101345596

07650...7LV+5LV Trilux Light colour: 4000 K Protection category: IP20
 E-Line

