






LED safety luminaire with optimised light distribution for the illumination of escape routes with high mounting heights. LED carrier for Trilux E-Line trunking system 7650...7LV + 5LV with stainless steel snap locks that can be applied tool-free. Automatic electrical connection by a plug-in contact with circuit selection. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Illuminant:	replaceable 1 x 3,5W LED-module	Apparent power:	7,6 VA
Luminous flux:	531 lm	Effective power:	5,7 W
Nominal voltage AC:	230V ±10% 50/60 Hz	Inrush current:	6 A / 98 µs
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	33 mA	Temperature ta:	-15...+40 °C
Nominal current DC:	25 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

	13.0	14.0	15.0	16.0
0.0	0.0	0.0	2.7	0.0
8.6	8.7	9.0	9.1	
27.6	27.8	27.6	26.9	
8.4	7.9	7.2	6.1	

Articles

SN LINE E - 12 AHB LED J/SV		Name	Accessories	Art. no.
Colors	RAL 9016	J-ET 5.1 SV-max. 24V DC320mA const.	spare part	101422893
Art. no.	101321853			

07650...7LV+5LV Trilux E-Line Light colour: 4000 K Protection category: IP20

