


LED safety luminaire with optimised light distribution for the illumination of areas with high mounting heights. LED carrier for Trilux E-Line trunking system 7650...7LV + 5LV with stainless steel snap locks that can be applied tool-free. Automatic electrical connection by a plug-in contact with circuit selection. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	sheet steel painted	Nominal current DC:	185 mA
Illuminant:	1 x 3,5W LED-module	Protection class:	I
Luminous flux:	545 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	⊘	⊘
6.0	6.9	17.5
6.5	7.0	18.1
7.0	7.1	18.6
7.5	7.1	19.0
8.0	6.9	19.3
8.5	6.7	19.6
9.0	6.3	19.8
9.5	5.8	20.0
10.0	5.2	20.1

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

[m]	⊘	⊘
6.0	4.9	14.2
6.5	5.1	14.7
7.0	5.0	14.9
7.5	4.9	16.2
8.0	4.7	16.3
8.5	4.7	16.8
9.0	4.6	17.5
9.5	4.5	17.7
10.0	4.3	16.6

Articles

SN LINE E - 12 SHB LED 24V

Colors RAL 9016
Art. no. 101345495

07650...7LV+5LV Trilux E-Line Light colour: 4000 K Protection category: IP20

