


LED safety luminaire with optimised light distribution for the illumination of areas. LED carrier for Trilux E-Line trunking system 7650...7LV + 5LV with stainless steel snap locks that can be applied tool-free. Automatic electrical connection by a plug-in contact with circuit selection. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	sheet steel painted	Nominal current DC:	185 mA
Illuminant:	1 x 3,5W LED-module	Protection class:	I
Luminous flux:	517 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance [m]	2.5	5.9	15.2
2.5	3.0	5.9	16.3
3.5	5.9	16.7	
4.0	5.8	16.9	
4.5	5.6	16.8	
5.0	5.0	16.7	
5.5	3.8	16.4	
6.0	1.4	16.2	

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Distance [m]	2.5	4.5	12.6
2.5	3.0	4.9	14.0
3.5	5.0	14.9	
4.0	4.6	15.5	
4.5	4.1	15.1	
5.0	3.9	14.5	
5.5	3.7	14.3	
6.0	3.5	14.1	

Articles

SN LINE E -12 SLB LED 24V

Colors	RAL 9016	
Art. no.	101345394	
07650...7LV+5LV Trilux E-Line	Light colour: 4000 K	Protection category: IP20

