





LED safety luminaire with optimised light distribution for the illumination of escape routes. LED carrier for Trilux E-Line NEXT FIX trunking system 07650Fi L... 7+7LV... or 07650Fi... 7LV+5LV... with snap locks that can be applied tool-free. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Illuminant:	replaceable 1 x 0,9W LED-module	Effective power:	1,6 W
Luminous flux:	139 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C
Nominal current DC:	65 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

2.5	6.2	16.4	5.2	1.8
3.0	4.8	17.1	5.3	1.8
3.5	4.4	16.5	5.3	1.6
4.0	3.4	14.2	5.2	1.3
4.5	2.7	13.5	4.9	0.8

Articles

SN LINE FIX E-03 ALB LED 24V			
Colors	RAL 9005	RAL 9006	RAL 9016
Art. no.	101351256	101351155	101351054

07650Fi L... 7+7LV... or Light colour: 4000 K Protection category: IP20
07650Fi... 7LV+5LV... Trilux E-LI-NE NEXT FIX

Name	Accessories	Art. no.
L-JET 3 - max. 24V DC, 320mAconst	spare part	101421176

