





LED safety luminaire with optimised light distribution for the illumination of escape routes with high mounting heights. LED carrier for Trilux trunking system E-Line PRO 078...13 LV with snap locks that can be applied tool-free. Incl. 4-chip LED illuminant for maximum safety.

Technical data

Illuminant:	replaceable 1 x 3,5W LED-module
Luminous flux:	531 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	25 mA
Nominal current DC:	25 mA

Apparent power:	5,8 VA
Effective power:	5,5 W
Inrush current:	6 A / 34 µs
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

	13.0	14.0	15.0	16.0
0.0	0.0	0.0	2.7	0.0
8.6	8.6	8.7	9.0	9.1
27.6	27.6	27.8	27.6	26.9
8.4	8.4	7.9	7.2	6.1

Articles

SN LINE PRO -12 AHB FLD 230V			
Colors	RAL 9005	RAL 9006	RAL 9016
Art. no.	104722311	104721196	104719984
Trilux E-Line PRO 078...13 LV Light colour: 4000 K Protection category: IP50			

