





LED safety luminaire with optimised light distribution for the illumination of areas with high mounting heights. LED carrier for Trilux trunking system E-Line PRO 078...13 LV with snap locks that can be applied tool-free. Incl. 4-chip LED illuminant for maximum safety.

Technical data

Illuminant:	replaceable 1 x 3,5W LED-module	Effective power:	4,6 W
Luminous flux:	545 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C
Nominal current DC:	190 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

6.0	6.9	17.4
6.5	7.0	17.9
7.0	7.0	18.4
7.5	7.0	18.8
8.0	6.9	19.2
8.5	6.6	19.5
9.0	6.2	19.7
9.5	5.7	19.8
10.0	5.0	19.9

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

6.0	4.9	14.2
6.5	5.1	14.7
7.0	5.0	14.9
7.5	4.9	16.2
8.0	4.7	16.3
8.5	4.7	16.8
9.0	4.6	17.5
9.5	4.5	17.7
10.0	4.3	16.6

Articles

SN LINE PRO -12 SHB LED 24V

Colors	RAL 9005	RAL 9006	RAL 9016
Art. no.	104721705	104720590	104719378

Trilux E-Line PRO 078...13 LV Light colour: 4000 K Protection category: IP50

