





LED safety luminaire with optimised light distribution for the illumination of areas. LED carrier for Trilux trunking system E-Line PRO 078...13 LV with snap locks that can be applied tool-free. Incl. 4-chip LED illuminant for maximum safety.

Technical data

Illuminant:	replaceable 1 x 3,5W LED-module	Effective power:	4,6 W
Luminous flux:	517 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C
Nominal current DC:	190 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

2.5	4.6	12.8
3.0	4.6	13.1
3.5	4.3	13.2
4.0	3.7	13.1
4.5	2.2	12.7

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

2.5	3.7	11.7
3.0	3.7	12.3
3.5	3.2	12.8
4.0	2.9	12.3
4.5	2.6	12.3
5.0	2.4	12.3
5.5	2.2	10.8
6.0	2.0	9.9

Articles

SN LINE PRO -12 SLB LED 24V

Colors	RAL 9005	RAL 9006	RAL 9016
Art. no.	104721604	104720489	104719277

Trilux E-Line PRO 078...13 LV Light colour: 4000 K Protection category: IP50

