





LED safety luminaire with optimised light distribution for the illumination of areas. LED carrier for Trilux trunking system E-Line PRO 078...13 LV with snap locks that can be applied tool-free. Incl. 4-chip LED illuminant for maximum safety.

Technical data

Illuminant:	replaceable 1 x 3,5W LED-module	Apparent power:	7,6 VA
Luminous flux:	517 lm	Effective power:	5,7 W
Nominal voltage AC:	230V ±10% 50/60 Hz	Inrush current:	6 A / 98 µs
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	33 mA	Temperature ta:	-15...+40 °C
Nominal current DC:	25 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter (m)	2.5	5.8	15.1
2.5	5.8	15.1	
3.0	5.9	16.1	
3.5	5.8	16.5	
4.0	5.7	16.7	
4.5	5.4	16.6	
5.0	4.9	16.5	
5.5	3.7	16.3	
6.0	1.4	15.9	

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Beam diameter (m)	2.5	4.5	12.6
2.5	4.5	12.6	
3.0	4.9	14.0	
3.5	5.0	14.9	
4.0	4.6	15.5	
4.5	4.1	15.1	
5.0	3.9	14.5	
5.5	3.7	14.3	
6.0	3.5	14.1	

Articles

SN LINE PRO -12 SLB LED J/SV

Colors	RAL 9005	RAL 9006	RAL 9016
Art. no.	104721200	104720085	104718873

Trilux E-Line PRO 078...13 LV Light colour: 4000 K Protection category: IP50

