





LED safety luminaire with optimised light distribution for the illumination of areas. LED carrier for Trilux trunking system E-Line PRO 078...13 LV with snap locks that can be applied tool-free. Incl. 4-chip LED illuminant for maximum safety.

Technical data

Illuminant:	replaceable 1 x 3,5W LED-module
Luminous flux:	517 lm
Nominal voltage DC:	24 V $\pm$ 25 %
Nominal current DC:	190 mA

Effective power:	4,6 W
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

2.5	4.6	12.8
3.0	4.6	13.1
3.5	4.3	13.2
4.0	3.7	13.1
4.5	2.2	12.7

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

2.5	3.7	11.7
3.0	3.7	12.3
3.5	3.2	12.8
4.0	2.9	12.3
4.5	2.6	12.3
5.0	2.4	12.3
5.5	2.2	10.8
6.0	2.0	9.9

Articles

SN LINE PRO -12 SLB LED 24V

Colors	RAL 9005	RAL 9006	RAL 9016
Art. no.	104718065	104716853	104715641

Trilux E-Line PRO 078...13 LV Light colour: 4000 K Protection category: IP20

