




Combined luminaire for general and emergency lighting Luminaire with targeted light output. Robust trapezoidal luminaire housing for wall mounting made of powder-coated die-cast aluminium. High protection rating for outdoor installation. And optional cable entry at the side. Incl. four cable entries for through-wiring to general and emergency lighting. Externe voedingsunit: IP66; Ta: -5...+40 °C


**Technische gegevens**

<b>Bedrijfsduur:</b>	1h;1,5h;2h;3h;8h	<b>Opgen. vermogen:</b>	5,5 W
<b>Batterij type:</b>	Ni-MH 4,8 V 1,1 Ah	<b>Inschakelstroom:</b>	11 A / 64 µs
<b>Materiaal:</b>	Gegoten aluminium	<b>Beschermingsklasse:</b>	I
<b>Lichtbron:</b>	9 x 0,32W LED module	<b>Rijgklem:</b>	max. 2,5mm <sup>2</sup> aderdikte
<b>Nom. spanning AC:</b>	230V AC ±10% 50/60 Hz	<b>Temperatuurbereik:</b>	-15...+40 °C
<b>Nom. stroom AC:</b>	28 mA	<b>Slagvastheid:</b>	IK09
<b>Schijnb. vermogen:</b>	6,5 VA		

**Technische gegevens (algemene verlichting)**

<b>Nom. spanning AC:</b>	230V AC/DC ±10% 50/60 Hz	<b>Lichtkleur:</b>	3000 K
<b>Schijnb. vermogen:</b>	12,5 VA	<b>Lumenoutput:</b>	918 lm
<b>Leistung (Allgemeinlicht):</b>	10,4 W	<b>Inschakelstroom:</b>	8 A / 50 µs



Plafondmontage: Minimale verlichtingsterkte 1,0lx op de het hart van de vluchtroute, onderhoud factor 0,8




Distance to middle of escape route	Distance to middle of escape route						
	1.0m	2.0m	3.0m	1.0m	2.0m	3.0m	
<b>1h</b> (65%)	1.0	2.3	5.6	1.9	5.2	0.0	0.0
	2.0	3.2	7.8	3.1	7.8	2.5	7.1
	3.0	3.7	9.2	3.6	9.3	3.2	8.9
	4.0	3.9	10.1	3.9	10.4	3.6	10.1
	5.0	3.9	10.7	4.0	11.0	3.7	10.8
<b>3h</b> (30%)	1.0	1.8	4.5	1.1	3.6	0.0	0.0
	2.0	2.5	6.2	2.1	5.9	0.9	4.7
	3.0	2.7	7.2	2.5	7.0	1.7	6.2
	4.0	2.6	7.6	2.4	7.5	1.6	6.9
	5.0	2.1	7.5	1.9	7.5	0.6	6.9
<b>8h</b> (15%)	1.0	1.2	4.0	0.0	0.0	0.0	0.0
	2.0	1.5	3.4	0.0	0.0	0.0	0.0
	3.0	1.1	5.5	0.0	0.0	0.0	0.0

**Artikel**

BN/A/V 6201 SV/B LED 1-8/D						
Kleuren	DB 703	HWF 7015	RAL 7015	RAL 9016	HWF 9016	HWF (speciale)
Art. Nr.	104365128	104365330	104364926	104364825	104365229	104365431
Wandmontage		Lichtkleur: 3000 K			Bescherming: IP65	

**BN noodunit AP SV/B LED - 1-8/D SKII IP66** Art. Nr. 102024091

benodigd



<b>Omschrijving</b>	<b>Accessoires</b>	<b>Art. nr.</b>
BN noodunit AP SV/B LED - 1-8/D SKII IP66	benodigd	102024091
mounting adapter 6201 RAL 7015	optioneel	104575292