




Luminaire with targeted light output. Robust trapezoidal luminaire housing for wall mounting made of powder-coated die-cast aluminium. High protection rating for outdoor installation. And optional cable entry at the side.


Technische gegevens

Materiaal:	Gepoedercoat gegoten aluminium
Lichtbron:	18 x 0,3W LED module
Lumenoutput:	687 lm
Nom. spanning AC:	230V ±10% 50/60 Hz
Nom. spanning DC:	176 - 264 V
Nom. stroom AC:	40 mA
Nom. stroom DC:	35 mA

Schijnb. vermogen:	9,3 VA
Opgen. vermogen:	9,0 W
Inschakelstroom:	6 A / 22 µs
Beschermingsklasse:	I
Rijgklem:	max. 2,5 mm ² aderdikte
Temperatuurbereik:	-15...+40 °C
Slagvastheid:	IK09

Technische gegevens (algemene verlichting)

Lumenoutput:	687 lm
---------------------	--------




Wandmontage: Minimale verlichtingsterkte 1,0lx

	1.0m	2.0m	3.0m
1.0	3.1	7.4	3.0
1.5	3.8	9.1	3.8
2.0	4.4	10.4	4.4
2.5	4.8	11.6	4.9
3.0	5.2	12.6	5.3
3.5	5.5	13.5	5.6
4.0	5.8	14.2	5.9
4.5	6.0	14.9	6.2
5.0	6.2	15.5	6.4
5.5	6.4	16.0	6.5
6.0	6.5	16.5	6.7

Artikel


SN 6201 -06 FLD 230V					
Kleuren	DB 703	HWF 7015	RAL 7015	RAL 9016	HWF 9016
					HWF (speciale)
Art. Nr.	104362300	104362502	104362195	104362094	104362401
					104362603

Wandmontage Lichtkleur: 3000 K Bescherming: IP65



mounting adapter 6201 RAL 7015

Art. Nr. 104575292



Omschrijving	Accessoires	Art. nr.
FLD 230/8 - CC - 650 - C		100903440
LM 176x20 18/3K KL LED Modul		104412113
mounting adapter 6201 RAL 7015	optioneel	104575292